

Aroma

Perfect taste

Friulinox




Aroma

Friulinox

1

EN



Always perfect results
Responsive humidity management



Ideal climate
Automatic climate change management




Easy to use
5" touch screen color display
with control interface



Experience at your service
The know-how of the best experts
at your disposal



Maximum Visibility
LED door lighting




Flexibility
Wide range of customization possibilities




Energy saving
Double glazed door with
high insulation level



Ideal for any installation
High efficiency tropicalized
refrigeration unit.



Create your layout
Model modularity



Easy to clean
Lower infill plinth

Based on the experience of Friulinox preservation systems, the new **Aroma** seasoning and maturation cabinets were created. Equipped with the most sophisticated temperature, humidity and ventilation controls that generate **the perfect microclimate for each specific type of product**. Two distinguishable versions are available. The Front is designed to give an elegant TOTAL BLACK aesthetic with internal LED lighting that enhances the product and makes it easy to insert as a visible design element in any environment. It can be customized with a **wide range of accessories according to the type of food to be stored**. The Back version, on the other hand, is completely made in stainless steel with a blind door which makes it suitable for installation inside a laboratory or a maturing warehouse.



Meat

Model	Dimensions (L x P x H mm)	Load volume (L)	Temperature Range	Humidity control	Refrigerant gas	Power (W)	Absorption (A)	Power supply (V-ph/1N/Hz)
CSASG1VA	780 x 900 x 2090	510	-2/+5 °C	Si	R134a	750	4,5	220-240/1N-/50

Cured meat

Model	Dimensions (L x P x H mm)	Load volume (L)	Temperature Range	Humidity control	Refrigerant gas	Power (W)	Absorption (A)	Power supply (V-ph/1N/Hz)
CSASG1VA	780 x 900 x 2090	510	-2/+10 °C	Si	R134a	750	4,5	220-240/1N-/50

Cheese

Model	Dimensions (L x P x H mm)	Load volume (L)	Temperature Range	Humidity control	Refrigerant gas	Power (W)	Absorption (A)	Power supply (V-ph/1N/Hz)
CSASG1VA	780 x 900 x 2090	510	-2/+10 °C	Si	R134a	750	4,5	220-240/1N-/50

* special voltages and frequencies on request

Aroma

RF54LO0068

FRIULINOX - ALI GROUP Srl a Socio Unico
Via Treviso 4 - 33083 Taiedo di Chions (PN) ITALY
Tel. +39 0434 635411 - Fax +39 0434 635414

info@friulinox.com | www.friulinox.com

The data and information may change based on the continual development of products.
See the complete range on: www.friulinox.com

an Ali Group Company



The Spirit of Excellence