

Vanilla

Perfect flavour

Friulinox

3.7 °C 42%

Vanilla

Friulinox

1

EN



100% guarantee for your customers

Product management app for Sushi SFC conservation



Easy to use

2.8" captive color display with control interface



Always perfect storage

Humidity control via hygrometric probe



Respecting the environment

High efficiency tropicalized refrigeration unit in climate class 5, with R290 gas



Everything under control

Connectivity with HACCP remote control

From the cold specialists comes the new line of **Vanilla** cabinets, dedicated to the world of pastry and ice cream, which are **available in different temperatures, according to the products to be stored**, with tray sizes **EN1, EN2, and ICE**. Thanks to the different technological solutions for temperature and humidity control, they always guarantee perfect product conservation. It was precisely from the need to be able to always guarantee the best preserved product that a specific APP, called Sushi SFC Smart Freshness Control, was made available. It was created to give you everything under control. The App alerts you to when the food inside is expiring or has expired, which avoids waste and eliminates the risk of using products that are no longer suitable for consumption.



Pastry

| Model | Dimensions (L x P x H mm) | Capacity trays | Temperature Range | Refrigerant gas | Power (W) | Absorption (A) | Power supply (V-ph/1N/Hz) |
|----------|------------------------------|-------------------|----------------------|-------------------|--------------|-------------------|------------------------------|
| CRV11A | 780 x 730 x 2090 | 20 x EN1 | -2/+8 °C | R290 | 154 | 0,71 | 220-240/1N-/50 |
| CRV11W | 780 x 730 x 2090 | 20 x EN1 | -2/+8 °C | R290 | 154 | 0,71 | 220-240/1N-/50 |
| CRV11-P | 780 x 730 x 2090 | 20 x EN1 | -2/+8 °C | R134a | 410 | 2,08 | 220-240/1N-/50 |
| CRV21A | 780 x 1010 x 2090 | 20 x EN2 | -2/+8 °C | R290 | 202 | 0,95 | 220-240/1N-/50 |
| CRV21W | 780 x 1010 x 2090 | 20 x EN2 | -2/+8 °C | R290 | 202 | 0,95 | 220-240/1N-/50 |
| CRV21-P | 780 x 1010 x 2090 | 20 x EN2 | -2/+8 °C | R134a | 480 | 2,44 | 220-240/1N-/50 |
| CFV11A | 780 x 730 x 2090 | 20 x EN1 | -25/-15 °C | R290 | 314 | 2,02 | 220-240/1N-/50 |
| CFV11W | 780 x 730 x 2090 | 20 x EN1 | -25/-15 °C | R290 | 314 | 2,02 | 220-240/1N-/50 |
| CFV11-P | 780 x 730 x 2090 | 20 x EN1 | -25/-15 °C | R452a/R448a/R449a | 710 | 3,60 | 220-240/1N-/50 |
| CFV21A | 780 x 1010 x 2090 | 20 x EN2 | -25/-15 °C | R290 | 528 | 3,84 | 220-240/1N-/50 |
| CFV21W | 780 x 1010 x 2090 | 20 x EN2 | -25/-15 °C | R290 | 528 | 3,84 | 220-240/1N-/50 |
| CFV21-P | 780 x 1010 x 2090 | 20 x EN2 | -25/-15 °C | R452a/R448a/R449a | 740 | 3,75 | 220-240/1N-/50 |
| CRVP11A | 780 x 730 x 2090 | 20 x EN1 | -2/+18 °C | R290 | 154 | 0,71 | 220-240/1N-/50 |
| CRVP11W | 780 x 730 x 2090 | 20 x EN1 | -2/+18 °C | R290 | 154 | 0,71 | 220-240/1N-/50 |
| CRVP11-P | 780 x 730 x 2090 | 20 x EN1 | -2/+18 °C | R134a | 410 | 2,08 | 220-240/1N-/50 |
| CRVP21A | 780 x 1010 x 2090 | 20 x EN2 | -2/+18 °C | R290 | 202 | 0,95 | 220-240/1N-/50 |
| CRVP21W | 780 x 1010 x 2090 | 20 x EN2 | -2/+18 °C | R290 | 202 | 0,95 | 220-240/1N-/50 |
| CRVP21-P | 780 x 1010 x 2090 | 20 x EN2 | -2/+18 °C | R134a | 480 | 2,44 | 220-240/1N-/50 |

* also available in glass door version

Ice cream making

| Model | Dimensions (L x P x H mm) | Capacity trays | Temperature Range | Refrigerant gas | Power (W) | Absorption (A) | Power supply (V-ph/1N/Hz) |
|---------|------------------------------|----------------------------|----------------------|-------------------|--------------|-------------------|------------------------------|
| CGVG1A | 780 x 900 x 2090 | 54 pz 165 x 360 mm H 120mm | -25/-12 °C | R290 | 528 | 3,84 | 220-240/1N-/50 |
| CGVG1W | 780 x 900 x 2090 | 54 pz 165 x 360 mm H 120mm | -25/-12 °C | R290 | 528 | 3,84 | 220-240/1N-/50 |
| CGVG1-P | 780 x 900 x 2090 | 54 pz 165 x 360 mm H 120mm | -25/-12 °C | R452a/R448a/R449a | 740 | 3,75 | 220-240/1N-/50 |

* special voltages and frequencies on request

FRIULINOX - ALI GROUP Srl a Socio Unico
Via Treviso 4 - 33083 Taiedo di Chions (PN) ITALY
Tel. +39 0434 635411 - Fax +39 0434 635414

info@friulinox.com | www.friulinox.com

The data and information may change based on the continual development of products. See the complete range on: www.friulinox.com

RF54LO0054

an Ali Group Company



The Spirit of Excellence