

# MULTI ECO HOOD FOR BACKMASTER EB 30<sup>MT</sup>

## MODULAR SOLUTIONS

INSTALLED IN THE FACTORY - RIGHT/LEFT



### HIGHLIGHTS

- EB 30<sup>MT</sup> for switching on and fully automatic control
- Air-cooled plate condensers for condensing vapours during baking
- Fan shut-off delay approx. 5 min
- Continuous drainage of condensation
- 2 fan speed levels

### Technical data

Overall connection data	Dimensions
Voltage: 230 V/1 N AC	Width: 600 mm
Rated consumption: 0.06 kW	Depth: 638 mm
Rated current: < 1.0 Amp	Height: 150 mm
Fuse protection: 1 x 16 Amp (via EB 30 <sup>MT</sup> )	Weight: approx. 12 kg
Cable cross section: 1.5 mm <sup>2</sup>	Noise emission: < 70 dB (A)
	Air rate: 648 m <sup>3</sup> /h
Article number: EL0504141	

### Equipment/Version

- Compact attachment unit
- Flush device contour without protrusion
- Air flow deflector plates attached for easy cleaning
- Condensation system consisting of 4 plate condensers (1.8 m<sup>2</sup>)
- 4 low-noise axial fans for air cooling
- Spray water protection IP X5
- No additional installations required for power supply or waste water
- Electrical activation / power supply from combi steamer
- Condensation drain connected directly to the device drain
- No external power connection or condensation lines

